

7211X

Brand: Viper
Product Code: 7211X-7211V
Availability: 1
UPC: 093207062957
FCC ID: EZSDEI7211
MPN: 7211X
Location: Cleveland, OH

Price: \$89.99

Short Description

Clifford 2-Way 1-Button LED Remote

Description

Brand NEW Viper 7211V For Discontinued Clifford 7211X Responder 2-way LED Remote Control Transmitter.

The Clifford 7211X LED 2-Way remote control transmitter is Clifford's first generation LE 1-button remote control transmitter that started an industry trend and is DISCONTINUED. This Viper 7211V replacement remote control is the direct replacement for the Clifford remote control and made to fit the user's hand comfortably, enabling effortless and intuitive single-handed operation. This remote works with many Viper, Python, AutoMate, AstroStart and Clifford system

Whether you're replacing a lost remote or adding an extra for convenience, this 7211V is the perfect solution. Shop with confidence at Access 1 Alarm and Audio — where you'll receive a, new **GENUINE** remote control direct from the original manufacturer. No knock-offs. No reprogrammed returns. Just authentic Viper, Clifford and Python quality.

What you will receive:

- New 7211V 2-Way Remote Control
- Programming Instructions

Works with the following Clifford systems

- 4203X
- 4205X
- 4218X
- 9211X
- Responder One

Works with the following Python systems

- 4203P
- 4205P
- 4218P
- 9211P
- Responder One

Works with the following Viper systems

- 4203V
- 4205V
- 4211V
- 4218V
- 9211V
- Responder One

Please make sure you have a working control unit installed in the vehicle prior to ordering this remote control. Programming instructions are included with the package and will require accessing your valet/programming switch. Video instructions will be available on our YouTube page under remote controls. Please contact us if you have any questions.

Why buy from us? Well, we are the experts that only believe in perfection, from the quality of our images to the accurate description in each and every listing.

Programming Your Remote Control

Note: Make sure the system is disarmed, and the LED is off a minimum of 60-seconds prior to beginning the remote pairing process.

Preparing the system that HAS remote start

1. Open drivers door
2. Turn the ignition ON.
3. Within 10-seconds, press and release the valet and programming button once, then press and hold the system's valet/programming push-button. The status LED begins flashing and the siren/horn (if connected) sounds to confirm the system is ready for pairing. **DO NOT LET GO OF THE SWITCH**
4. Press the "START" button of the 7211 transmitter. The vehicles horn/siren will honk if connected. You have now successfully learned the remote to the vehicles remote start system.
5. Turn the ignition OFF and WAIT approximately 60 seconds.

Note: 2-Way remotes will emit tones and provide visual confirmation that the remote has successfully paired with the system.

[YouTube Channel Link](#)

Please contact us if you have any questions.

Product Gallery