

## 7656V



**Brand:** Viper  
**Product Code:** 7656V-7657V  
**Availability:** 4  
**UPC:** 093207096761  
**FCC ID:** EZS7657V  
**MPN:** 7656V-7657V  
**Location:** Cleveland, OH

**Price: \$56.99**

### Short Description

Viper 1-Way 1-Mile Remote Control

### Description

**Introducing The NEW Viper 7657V 1-Way Remote Control Transmitter  
Replacing The Older Viper 7656V**

Upgrade your Viper security, remote start or security with remote start system with this newly redesigned Viper 7657V 1-Way remote control, built to pair seamlessly with the latest Viper systems including the Digital DS3 - DS4 Systems, along with the legacy analog systems with the proper antenna - See list below.

The 7657V features a sleek, ergonomic design that fits comfortably in your hand or pocket, along with durable construction built for everyday use - No more broken key rings. Regardless if you need a replacement for a lost or damaged remote or simply want an extra transmitter, this genuine Viper remote control delivers dependable performance and seamless integration with your system when properly programmed.

Whether you're replacing a lost remote or adding an extra for convenience, the 7657V is the perfect solution. Shop with confidence at Access 1 Alarm and Audio — where you'll receive a brand-new, **GENUINE** remote control direct from the

original manufacturer. No knock-offs. No reprogrammed returns. Just authentic Viper quality.

**Works with the following Viper systems:**

- 3606V
- 3706V
- 3806V
- 4606V
- 4706V
- 4806V
- 5606V
- 5706V
- 5806V
- 5808V
- 5908V
- DS3
- DS3+
- DS4
- DS4+
- DS4V
- DS4VP
- DS4756V
- 9656V
- 9756V
- 9856V
- D9656V
- D9657V
- D9756V
- D9856V
- D9857V
- D9957V

**Will also work with the following Discontinued Clifford Matrix systems**

- 3606X
- 3706X
- 3806X
- 4606X
- 4706X
- 4806X

- 5606X
- 5706X
- 5806X
- 9656X
- 9756X
- 9856X
- D9656X
- D9756X
- D9856X

**Will also work with the following Discontinued Python systems**

- 4606P
- 4706P
- 4806P
- 5606P
- 5706P
- 5806P
- 9656P
- 9756P
- 9856P
- D9756P
- D9857P

**Works with the following Discontinued Autostart systems:**

- DS3
- DS3+
- DS4
- DS4+
- DS4AF
- DS4AFP
- DS4V
- DS4VP
- AS-2386TWS
- AS-RFD1554
- AS-RFD3520
- AS-RFD7506

## **Works with the following Discontinued Polar Start and Premier Defense systems:**

- PS-7880TWS
- PS-4686TWS
- PD485

## **Will also work with the following Antennas**

- 6816T
- 6826T
- A6827T
- 6866T
- 6867T
- A6868T

Please make sure you have a working control unit installed in the vehicle prior to ordering this remote control. Programming instructions are included with the package and will require accessing your windshield mounted valet/programming switch. Video instructions will be available on our YouTube page under remote controls.

## **Programming Your Remote Control**

**Note:** Make sure the system is disarmed, and the Control Center LED is completely OFF for a minimum of 60-seconds prior to beginning the remote pairing process.

### Preparing the system

1. Driver's door OPEN
2. Turn the ignition ON.
3. Within 10-seconds, press and release once, then press and hold the system's Control Center (The Windshield Mounted Antenna) Valet button. The status LED begins flashing and the siren/horn (if connected) sounds to confirm the system is ready for pairing.
4. Release the Control Center's Valet button.

## Pairing the remote control

1. Press and hold the UNLOCK button (approximately 8-seconds) until the remote enters pairing mode and emits a long beep.
2. Release the UNLOCK button.
3. Within 2 seconds, Press and release UNLOCK once more.
4. After a short delay, the horn/siren sounds (if connected) and the Parking Lights flash to confirm the system has paired with the remote control.
5. Turn the ignition OFF and WAIT approximately 60 seconds for the remote control to exit pairing mode.

**Note:** 2-Way remotes will emit tones and provide visual confirmation that the remote has successfully paired with the system. 1-Way remotes do not offer pairing confirmation.

## Programming Instructions

### Programming Your Remote Control

**Note:** Make sure the system is disarmed, and the Control Center LED is completely OFF for a minimum of 60-seconds prior to beginning the remote pairing process.

## Preparing the system

1. Driver's door OPEN
2. Turn the ignition ON.
3. Within 10-seconds, press and release once, then press and hold the system's Control Center (The Windshield Mounted Antenna) Valet button. The status LED begins flashing and the siren/horn (if connected) sounds to confirm the system is ready for pairing.
4. Release the Control Center's Valet button.

## Pairing the remote control

1. Press and hold the UNLOCK button (approximately 8-seconds) until the remote enters pairing mode and emits a long beep.
2. Release the UNLOCK button.
3. Within 2 seconds, Press and release UNLOCK once more.
4. After a short delay, the horn/siren sounds (if connected) and the Parking Lights flash to confirm the system has paired with the remote control.

5. Turn the ignition OFF and WAIT approximately 60 seconds for the remote control to exit pairing mode.

**Note:** 2-Way remotes will emit tones and provide visual confirmation that the remote has successfully paired with the system. 1-Way remotes do not offer pairing confirmation.

### Specification

Remote Control	
Works With Antenna(s)	6816T 6826T A6827T 6866T 6867T A6868T
Battery Type	CR2032
FCC ID	EZS7657V
IC Number	1513A-7657
Frequency	915Mhz
Range	1-Mile+
1-Way or 2-Way	1-WAY