

101BP



Brand: Prestige

Product Code: 101BP - 105BP

Availability: 4

FCC ID: ELVATJB

MPN: 101BP - 105BP

Location: Cleveland, Ohio

Price: \$46.99

Short Description

Prestige 101BP 1-Way 1-Button Remote Control Replacement

Description

NEW Prestige 105BP For DISCONTINUED Prestige 101BP 1-Way Remote Control Transmitter

NEW Prestige 105BP remote control transmitter. Are you looking for a replacement Prestige remote control for your system or just need an additional remote control? Buy with confidence from Access 1 Alarm and Audio!

Whether you're replacing a lost remote or adding an extra for convenience, the 105BP is the perfect solution. Shop with confidence at Access 1 Alarm and Audio, where you'll receive a brand-new, **GENUINE** remote control direct from the original manufacturer. No knock-offs. No reprogrammed returns. Just authentic Prestige and Pursuit quality.

Works with the following Prestige - Pursuit systems:

- AS25C
- APS422E
- APS510C

- APS57
- APS57CA
- APS596C
- APS687C
- APS787C
- APS901C
- APS997C
- PRO9051E
- PRO9051I
- PRO9056C
- PRO9056I
- PRO9276C
- PRO9276I
- PRO9276TW
- PRO9556C
- PRO90556CA
- PRO90556I
- PRO9644C
- PRO9800
- PRO9801C
- PRO9801I

Will replace or work with the following Prestige - Pursuit remote controls

- 08SP
- 091BPR
- 093BPR
- 095BPR
- 1BP
- 1BPR
- 101BP
- 103BP
- 105BP
- 5BCR10P
- 5BCR10PR
- 5BCR14P

Please make sure you have a working control unit installed in the vehicle prior to ordering this remote control. Programming instructions are included with the package and will require accessing your valet/programming switch. Video instructions will be

available on our YouTube page under remote controls.

The Valet/Programming Switch is either the push-button that is on the windshield mounted antenna or is a black push-button hidden under your dashboard that the technician should have showed you when the system was installed. In some cases on the older systems it is a combination push-button and LED light. If you can't find it, you will have to look under the drivers side dash for the system brain. On the side of the brain is a blue 2 pin port that has a thin gauge grey wire and a black wire. Follow those wires to you end into the pushbutton. This is the button that will need accessed to program your remote controls. Is the blue port empty? Then you will need to purchase the valet/programming switch [CLICK HERE TO PURCHASE IN OUR STORE](#)

Programming Your Remote Control

Note: Make sure the system is disarmed, and the LED is off a minimum of 60-seconds prior to beginning the remote pairing process.

1. Turn the ignition ON.
2. Within 10-seconds, press and release the valet and programming button three times. The siren/horn (if connected) sounds to confirm the system is ready for pairing.
3. Press the "LOCK" button of the transmitter. The vehicles horn/siren will honk if connected. You have now successfully learned the remote to the vehicles remote start system.
4. Turn the ignition OFF and WAIT approximately 60 seconds.

Why buy from us? Well, we are the experts that only believe in perfection, from the quality of our images to the accurate description in each and every listing.

Programming Instructions

The Valet/Programming Switch is either the push-button that is on the windshield mounted antenna or is a black push-button hidden under your dashboard that the technician should have showed you when the system was installed. In some cases on the older systems it is a combination push-button and LED light. If you can't find it, you will have to look under the drivers side dash for the system brain. On the side of the brain is a blue 2 pin port that has a thin gauge grey wire and a black wire. Follow those wires to you end into the pushbutton. This is the button that will need accessed to program your remote controls. Is the blue port empty? Then you will need to purchase the

valet/programming switch [CLICK HERE TO PURCHASE IN OUR STORE](#)

Programming Your Remote Control

Note: Make sure the system is disarmed, and the LED is off a minimum of 60-seconds prior to beginning the remote pairing process.

1. Turn the ignition ON.
2. Within 10-seconds, press and release the valet and programming button three times. The siren/horn (if connected) sounds to confirm the system is ready for pairing.
3. Press the "LOCK" button of the transmitter. The vehicles horn/siren will honk if connected. You have now successfully learned the remote to the vehicles remote start system.
4. Turn the ignition OFF and WAIT approximately 60 seconds.

Specification

Remote Control	
Battery Type	CR2032
FCC ID	ELVATJB
Frequency	434Mhz
Range	1/4-MILE
1-Way or 2-Way	1-WAY